

SPECTRA BIMINI 300™ IGNITION PROTECTED WATERMAKER

PRODUCT SPECIFICATIONS

300 gal (1136 l) Production / Day Production / Hour 12.5 gal (47 l)

12v DC 18A / 24v DC 9A 15 Watts/1 gal 4 Watts/1 liter Power Requirement

110 lbs (50 kg) Weight

Pre Filters 2.5"x10" pleated polyester 5 micron

Controls Spectra Connect Remote Controller

Installation Requirements Dedicated thruhull, dry and well

ventilated area not to exceed 110°F/37°C

 $40^{\prime\prime} \times 2.5^{\prime\prime}$ High rejection spiral wound polyamide Membranes

Pump and Motor Brushless DC Motor and Magnetically

Coupled Pump

Salt Rejection 99.2%

Max 110°F/37°C Min 36°F/2°C Temperature Range

Baseline Conditions 33,000 PPM feed water at 77°F/25°C

pH Range 3-11 (typical seawater pH is 8)

Chlorine Tolerance O PPM

Warranty Spectra standard warranty

Shipping Weight 120 lbs (55 kg)

47"×23"×18" Shipping Dimensions

120cm x 59cm x 46cm







The new Bimini 300 is the only Watermaker that complies with CFR Ignition Protection regulations, making it a perfect choice for midsize outboard motor-powered vessels. The system is extremely quiet and energy efficient while reliably delivering up to 12.5 gallons of water per hour. The Bimini 300 features the Spectra Connect controller that allows you completely automate the operation of your watermaker as well as control it from a remote device and location. This simple, low maintenance watermaker will be a revolutionary addition to the Outboard Cruiser class of vessels.

FEATURES

- The only watermaker that complies with CFR 183.410/ISO 8846 for Ignition Protection for use on gasoline powered boats
- State of the Art Efficiency Brushless DC Motor and speed controller
- Completely automated with the Spectra Connect Controller Compact modular design with Spectra's unique Clark Pump for efficiency and reliability
- Low power consumption, can be run on batteries, solar, or wind power
- Magnetically coupled pump for whisper quiet operation
- Non-sparking components
- System includes installation kit, wired remote display, booster pump, and full tank switch
- Z±ION Compatible
- **Patent Pending**




SPECTRA BIMINI 300™ WATERMAKER



Feed Pump Module Depth 4.5'' / 11.4 cm





44" / 112 cm High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm

Optional Components



Wifi Module



Tank Level Sensor

Katadyn reserves the right to modify products

Katadyn Desalination LLC.

Spectra Watermakers 2220 S McDowell Blvd Ext Petaluma, CA 94954

TEL: 1-415-526-2780 FAX: 1-414-526-2787 E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com